

HDS PPB 4" Midwoofer



Type Number: 830870

Features:

The new High Definition Sound (HDS) PPB series is the culmination of Peerless working in close partnership with end users of Peerless-based audio products. With a deep understanding of customer requirements and needs, Peerless developed the proprietary and highly advanced Polypropylene Black (PPB) cone material used in the HDS PPB Series, creating a stiff but still dampened cone that remains stable even under the greatest sound pressures.



Driver Highlights: PPB diaphragm, 26 mm coil, AL

[Go to Application Notes.](#)

Specs:

Electrical Data

Nominal impedance	Zn	8	ohm
Minimum impedance	Zmin	5.6	ohm
Maximum impedance	Zo	30.8	ohm
DC resistance	Re	5.2	ohm
Voice coil inductance	Le	0.6	mH

T-S Parameters

Resonance Frequency	fs	77.6	Hz
Mechanical Q factor	Qms	3.19	
Electrical Q factor	Qes	0.65	
Total Q factor	Qts	0.54	
Ratio fs/Qts	F	144	
Force factor	Bl	4.8	Tm
Mechanical resistance	Rms	0.9	Kg/s
Moving mass	Mms	5.9	g
Suspension compliance	Cms	0.72	mm/N
Effective cone diameter	D	8.4	cm
Effective piston area	Sd	55	cm ²
Equivalent volume	Vas	3	ltrs
Sensitivity		87	dB
Ratio BL/√(Re)		2.1	


Power handling

100h RMS noise test (IEC)	--	W
Long-term Max System Power (IEC)	--	W
Max linear SPL (rms) @ power	--	dB/W
Short Term Max power	--	W

Voice Coil and Magnet Parameters

Voice coil diameter	26	mm
Voice coil height	12	mm
Voice coil layers	2	
Height of the gap	6	mm
Linear excursion +/-	3	mm
Max mech. excursion +/-	--	mm
Flux density of gap	--	mWb
Total useful flux	0.7	mWb
Diameter of magnet	81	mm
Height of magnet	15	mm
Weight of magnet	0.31	Kg

Frequency:



Mechanical Dimensions:

